JOB SAFETY ANALYSIS (JSA)									
FORMAT NO: ER 5/10- F2.									
Department Ash pond	Equipment Ash pond.	Job description: Earth over Ash Pond 'A' of ITF	•						
Company	Orissa Pow	I er Generation Corporation	Date of Issue :	Date of Issue : 18.10.2021					
Location	Ash Pond.IB-Thermal Power Station	Period of work	Reviewed By: A.P. Satapathy; Sr. Manager Civil		Signature				
Analysis By	Name : A.K.Panda.	Designation: Sr. Asst. Manager	Reccommended By(S.O):		Signature				
Name of associted OPGC:Mr.A.K.Panda. Contractor persons		tractor:Mr	Approved By(Factory Manager):		Signature				
PPE Required	Safety shoes, Helmet, dust ma	sk, Ear plug, safety glass	Revision By :		Signature				
Tools Required	Sprade, crowbar, hosepipe etc) .	Date of Rev :						
SEQUE	NCE OF BASIC STEPS	IDENTIFIED SAFETY, HEALTH &		RECOMMENDED SAFE JOB STEPS					
1.Excavation of earth & loading into vehicle.		1.Blowing of dust. Inhalation of dust.	Sprinkling of water & use of dust mask by workmen.						
(Excavation of earth from borrow area arranged by contractor and shifted to Ash Pond 'A'.)		2.Air pollution due to fugitive emission. 3.Tilting of excavator. Injury to workmen.	Excavation to be done carefully. Rigidity of area soil near excavator post to be ensured.						
Reversing the Vehicle on the narrowdyke.		Hitting with the Vehicles/ persons during loading.	Loading to be done carefully. No person will be allowed to stay within the swing area of b excavator. Vehicles will be fixed with back gear alarms.						
		2.Tilting of vehicle as the road is narrow at places.	2. Adequte Supervison to be made.						
		3.Road accident	3.All vehicles will have valid documents like R.C.Book, Insurance, Fitness certificate etc.						
		4.Blowing of dust due to movement of vehicle.	4.The driver will have valid driving licence and shall not drive in alcholic condition.						
			5.The vehicle should lmit the speed to 10 KM/Hr on the dyke.						
			6.The driver must be accompanied with an assistant/helper.						
		5.Blockage of road.	7.Sprinkling of water over the road is to be ensured.						
			8.Vehicle should not to be parked on the road.						
			9.The braking system of Vehicles should be perfect.						

JOB SAFETY ANALYSIS (JSA)								
FORMAT NO: ER 5/10- F2.								
Department	Equipment	Job description: Eart	h Capping	JSA Serial No				
Ash pond	Ash pond.	over Ash Pond 'A' of IT	PS					
SEQUENCE OF BASIC STEPS		IDENTIFIED SAFETY, HEALTH &		RECOMMENDED SAFE JOB STEPS				
			10.Tyre in good condition.					
			11.While park wheel.	ing the vehicle for loading/unloading, stoppers should be provided on both front & rea				
			12.Safety tria	ngle is to be fitted on the front side of vehicle for distinct visibility.				
				f the vehicle should be in good conditon and there should not be any holes/ ess in the body of the dala through which earth will come out & fall on the road.				
			14.The vehile	s should move on specific route as approved by Enggin-charge				
			15. Drivers ey	e test to be carried out.				
4. Spreading of ea	arth over ash.	Blowing of dust due to movement of vehicle. Blowing of ash. Injury due to slip of spades.	Sprinkling of water & use of dust mask by workmen. 2. Use of proper PPE.					
5.44 :	1.1	4.00	45.6.11.1					
5.Maintenance of	vehicles.	1.Oil spillage/ leakage.	1.Defect is to be attended as early as possible.					
				il is to be contained & cleaned.				
6. Review the job	while execution	Identify while working	1. Take appropriate action.					

Emergency Safety measure for the job if any: First-Aid box should be kept at site. Emergency telephone No. Fire - 777,222257 and Hospital 600,222243 should be intimated to the workmen. This should be discussed with all. A responsible person should be present throughout the working hours for supervision and carrying out the instruction of Engineer-in-charge at any instant of time. No workmen will be allowed in alcholic condition or without safety PPEs in the working area. Consider hazard during summer drinking water, ORS powder, Rest shed etc. should be provided at site.